

Lecture 7: Input-Output Models

[IFAC PB pg 24-33]

- Shift operators
- Pulse transfer operator
- Z-transform
- Pulse transfer function
- Poles and zeros
- Transformations between system representations

1

Shift Operators

Operators on time series

Assume $h = 1$ (the *sampling-time convention*)

Time series are doubly infinite sequences:

- $f(k) : k = \dots - 1, 0, 1, \dots$

Forward shift operator:

- denoted q
- $qf(k) = f(k + 1)$
- $q^n f(k) = f(k + n)$

2

Shift Operators

Backward shift operator:

- denoted q^{-1}
- $q^{-1}f(k) = f(k - 1)$
- $q^{-n}f(k) = f(k - n)$

3

Pulse Transfer Operator

Rewrite the state-space model using the forward shift operator:

$$\begin{aligned}x(k + 1) &= qx(k) = \Phi x(k) + \Gamma u(k) \\y(k) &= Cx(k) + Du(k)\end{aligned}$$

Eliminate $x(k)$, (assuming $x(0) = 0$):

$$\begin{aligned}x(k) &= (qI - \Phi)^{-1}\Gamma u(k) \\y(k) &= Cx(k) + Du(k) = C(qI - \Phi)^{-1}\Gamma u(k) + Du(k) \\&= [C(qI - \Phi)^{-1}\Gamma + D] u(k) = H(q)u(k)\end{aligned}$$

$H(q)$ is the *pulse transfer operator* of the system

Describes how the input and output are related.

4

Poles and Zeros (SISO case)

The pulse transfer function can be written as a rational function

$$H(q) = \frac{B(q)}{A(q)}$$

$\deg A = n =$ the number of states

$\deg B = n_b \leq n$

$A(q)$ is the characteristic polynomial of Φ , i.e.

$$A(q) = \det(qI - \Phi)$$

The *poles* of the system are given by $A(q) = 0$

The *zeros* of the system are given by $B(q) = 0$

5

Disk Drive Example

Recall the double integrator from the previous lecture:

$$\begin{aligned}\frac{dx}{dt} &= \begin{bmatrix} 0 & 1 \\ 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 1 \end{bmatrix} u \\y &= \begin{bmatrix} 1 & 0 \end{bmatrix} x\end{aligned}$$

Sample with $h = 1$:

$$\begin{aligned}\Phi &= e^{Ah} = \begin{bmatrix} 1 & 1 \\ 0 & 1 \end{bmatrix} \\ \Gamma &= \int_0^h e^{As} B ds = \begin{bmatrix} 0.5 \\ 1 \end{bmatrix}\end{aligned}$$

6

Disk Drive Example cont.

Pulse transfer operator:

$$H(q) = C(qI - \Phi)^{-1}\Gamma + D$$

$$= [1 \ 0] \begin{bmatrix} q-1 & -1 \\ 0 & q-1 \end{bmatrix}^{-1} \begin{bmatrix} 0.5 \\ 1 \end{bmatrix} = \frac{[1 \ 0]}{(q-1)^2} \begin{bmatrix} q-1 & 1 \\ 0 & q-1 \end{bmatrix} \begin{bmatrix} 0.5 \\ 1 \end{bmatrix}$$

$$= \frac{0.5(q+1)}{(q-1)^2}$$

Two poles in 1 and one zero in -1 .

7

From Pulse Transfer Operator to Difference Equation

$$y(k) = H(q)u(k)$$

$$A(q)y(k) = B(q)u(k)$$

$$(q^n + a_1q^{n-1} + \dots + a_n)y(k) = (b_0q^{n_b} + \dots + b_{n_b})u(k)$$

which means

$$y(k+n) + a_1y(k+n-1) + \dots + a_ny(k)$$

$$= b_0u(k+n_b) + \dots + b_{n_b}u(k)$$

This form is also known as the *input-output form*

8

Input-Output Form with Backward Shift

$$y(k+n) + a_1y(k+n-1) + \dots + a_ny(k)$$

$$= b_0u(k+n_b) + \dots + b_{n_b}u(k)$$

can be written as

$$y(k) + a_1y(k-1) + \dots + a_ny(k-n)$$

$$= b_0u(k-d) + \dots + b_{n_b}u(k-d-n_b)$$

where $d = n - n_b$ is the *pole excess* of the system (the number of pure time delays in the system)

9

The *reciprocal polynomial*

$$A^*(q) = 1 + a_1q + \dots + a_nq^n = q^n A(q^{-1})$$

is obtained from the polynomial A by reversing the order of the coefficients.

Now the system can instead be written as

$$A^*(q^{-1})y(k) = B^*(q^{-1})u(k-d)$$

10

Input-Output Example

Using forward shift

$$y(k+2) + 2y(k+1) + 3y(k) = 2u(k+1) + u(k)$$

can be written

$$(q^2 + 2q + 3)y(k) = (2q + 1)u(k)$$

Hence,

$$A(q) = q^2 + 2q + 3$$

$$B(q) = 2q + 1$$

11

Input-Output Example, continued

Using backward shift

$$y(k) + 2y(k-1) + 3y(k-2) = 2u(k-1) + u(k-2)$$

can be written ($d = 1$)

$$(1 + 2q^{-1} + 3q^{-2})y(k) = (2 + q^{-1})u(k-1)$$

Hence,

$$A^*(q^{-1}) = 1 + 2q^{-1} + 3q^{-2}$$

$$B^*(q^{-1}) = 2 + q^{-1}$$

12

Z-transform

The discrete-time counterpart to the Laplace transform

Defined on semi-infinite time series $f(k) : k = 0, 1, \dots$

$$\mathcal{Z}\{f(k)\} = F(z) = \sum_{k=0}^{\infty} f(k)z^{-k}$$

z is a complex variable

13

Example — Discrete-Time Step Signal

Let $y(k) = 1$ for $k \geq 0$. Then

$$Y(z) = 1 + z^{-1} + z^{-2} + \dots = \frac{z}{z-1}, \quad |z| > 1$$

Application of the following result for power series

$$\sum_{k=0}^{\infty} x^k = \frac{1}{1-x} \text{ for } |x| < 1$$

14

Example — Discrete-Time Ramp Signal

Let $y(k) = k$ for $k \geq 0$. Then

$$Y(z) = 0 + z^{-1} + 2z^{-2} + 3z^{-3} \dots = \frac{z}{(z-1)^2}$$

Application of the following result for power series

$$\sum_{k=0}^{\infty} kx^k = \frac{x}{(1-x)^2} \text{ for } |x| < 1$$

15

Z-transform Table

$f(k)$	$\mathcal{Z}(f(k))$
$\delta(k)$ (pulse)	1
1 (step)	$\frac{z}{z-1}$
k (ramp)	$\frac{z}{(z-1)^2}$
a^k	$\frac{z}{z-a}$

16

Some Properties of the Z-transform

\mathcal{Z} linear

$$\mathcal{Z}(q^{-n}f) = z^{-n}F(z)$$

$$\mathcal{Z}(qf) = z(F(z) - f(0))$$

$$\mathcal{Z}(f * g) = \mathcal{Z}\left\{\sum_{j=0}^k f(j)g(k-j)\right\} = (\mathcal{Z}f) \cdot (\mathcal{Z}g)$$

17

From State Space to Pulse Transfer Function

$$\begin{cases} x(k+1) = \Phi x(k) + \Gamma u(k) \\ y(k) = Cx(k) + Du(k) \end{cases}$$

$$\begin{cases} z(X(z) - x(0)) = \Phi X(z) + \Gamma U(z) \\ Y(z) = CX(z) + DU(z) \end{cases}$$

$$Y(z) = C(zI - \Phi)^{-1}z x(0) + [C(zI - \Phi)^{-1}\Gamma + D]U(z)$$

The rational function $H(z) = C(zI - \Phi)^{-1}\Gamma + D$ is called the *pulse transfer function* from u to y .

It is the Z-transform of the pulse response.

18

$H(q)$ vs $H(z)$

The pulse transfer operator $H(q)$ and the pulse transfer function $H(z)$ are the same rational functions

They have the same poles and zeros

$H(q)$ is used in the time domain ($q =$ shift operator)

$H(z)$ is used in the Z-domain ($z =$ complex variable)

19

Calculating System Response Using the Z-transform


1. Find the pulse transfer function $H(z) = C(zI - \Phi)^{-1}\Gamma + D$
2. Compute the Z-transform of the input: $U(z) = \mathcal{Z}\{u(k)\}$
3. Compute the Z-transform of the output:

$$Y(z) = C(zI - \Phi)^{-1}z x(0) + H(z)U(z)$$
4. Apply the inverse Z-transform (table) to find the output:

$$y(k) = \mathcal{Z}^{-1}\{Y(z)\}$$

20

Frequency Response in Continuous Time




Given a stable system $G(s)$, the input $u(t) = \sin \omega t$ will, after a transient, give the output

$$y(t) = |G(i\omega)| \sin(\omega t + \arg G(i\omega))$$

- The amplitude and phase shift for different frequencies are given by the value of $G(s)$ along the imaginary axes, i.e. $G(i\omega)$
- Plotted in Bode and Nyquist diagrams.

21

Frequency Response in Discrete Time




Given a stable system $H(z)$, the input $u(k) = \sin(\omega k)$ will, after a transient, give the output

$$y(k) = |H(e^{i\omega})| \sin(\omega k + \arg H(e^{i\omega}))$$

- $G(s)$ and the imaginary axis are replaced by $H(z)$ and the unit circle.
- Only describes what happens at the sampling instants
- The inter-sample behavior is not studied in this course

22


Bode diagram for continuous transfer function $1/(s^2 + 1.4s + 1)$ (solid) and for ZOH-sampled counterpart (dashed, plotted for $\omega h \in [0, \pi]$)



For slow signals, the hold circuit is approximately a $h/2$ delay. For fast signals, the hold circuit destroys the sinusoidal shape.

23

Nyquist diagram for cont. transfer function $1/(s^2 + 1.4s + 1)$ (solid) and for ZOH-sampled counterpart (dashed, plotted for $\omega h \in [0, \pi]$)



24


Interpretation of Poles and Zeros

Poles:

- A pole $z = a$ is associated with the time function $f(k) = a^k$


Zeros:

- A zero $z = a$ implies that the transmission of the input $u(k) = a^k$ is blocked by the system
- Related to how inputs and outputs are coupled to the states



25


Transformation of Poles: $z_i = e^{s_i h}$



26

New Evidence of the Alias Problem


Several points in the s -plane are mapped into the same point in the z -plane. The map is not bijective



27

Sampling of a Second Order System

$$G(s) = \frac{\omega_0^2}{s^2 + 2\zeta\omega_0 s + \omega_0^2}, \quad |\zeta| < 1$$



- Larger $\omega_0 \Rightarrow$ faster system response
- Smaller $\varphi \Rightarrow$ better damping (relative damping $\zeta = \cos \varphi$).
(Common choice: $\zeta = \cos 45^\circ = 0.7$)

28

Sampling of a Second Order System


The poles of the sampled system are given by

$$z^2 + a_1 z + a_2 = 0$$

where

$$a_1 = -2e^{-\zeta\omega_0 h} \cos(\sqrt{1-\zeta^2}\omega_0 h)$$

$$a_2 = e^{-2\zeta\omega_0 h}$$



29

Transformation of Zeros

- More complicated than for poles
- Extra zeros may appear in the sampled system
- There can be zeros outside the unit circle also if the continuous system has all the zeros in the left half plane
- For short sampling periods

$$z_i \approx e^{s_i h}$$

30

Calculation of $H(z)$ Given $G(s)$

Three approaches:

1. Make state realization of $G(s)$. Sample to get Φ and Γ . Then $H(z) = C(zI - \Phi)^{-1}\Gamma + D$.
2. Directly using the formula

$$H_{zoh}(z) = \frac{z-1}{z} \frac{1}{2\pi i} \int_{\gamma-i\infty}^{\gamma+i\infty} \frac{e^{sh}}{z - e^{sh}} \frac{G(s)}{s} ds$$

$$= \sum_{s=s_i} \frac{1}{z - e^{sh}} \text{Res} \left\{ \frac{e^{sh} - 1}{s} G(s) \right\}$$

- s_i are the poles of $G(s)$ and Res denotes the residue.
- outside the scope of the course

31

3. Use Table 2 (pg 28) in IFAC PB

- With care: The table gives the pulse transfer function for the ZOH-sampled transfer function $G(s)$. It does not give you the Z-transform for the signal with the Laplace transform $G(s)$.

$G(s)$	$H(z)$
$\frac{1}{s^2}$	$\frac{h^2(z+1)}{2(z-1)^2}$

For example, the Laplace transform of a ramp is $1/s^2$. However, the Z-transform of a ramp is not

$$\frac{h^2(z+1)}{2(z-1)^2}$$

(Do you remember what it is?)

32

Calculation of $H(z)$ Given $G(s)$

Example 1. For $G(s) = 1/s^2$, the previous lecture gave

$$\Phi = \begin{pmatrix} 1 & h \\ 0 & 1 \end{pmatrix} \quad \Gamma = \begin{pmatrix} \frac{h^2}{2} \\ h \end{pmatrix} \quad C = \begin{pmatrix} 1 & 0 \end{pmatrix}$$

With $h = 1$, this gives

$$H(z) = C(zI - \Phi)^{-1}\Gamma = \begin{pmatrix} 1 & 0 \end{pmatrix} \begin{pmatrix} z-1 & -h \\ 0 & z-1 \end{pmatrix}^{-1} \begin{pmatrix} \frac{h^2}{2} \\ h \end{pmatrix}$$

$$= \begin{pmatrix} 1 & 0 \end{pmatrix} \begin{pmatrix} (z-1)^{-1} & h(z-1)^{-2} \\ 0 & (z-1)^{-1} \end{pmatrix} \begin{pmatrix} \frac{h^2}{2} \\ h \end{pmatrix} = \frac{h^2(z+1)}{2(z-1)^2}$$

33

Calculation of $H(z)$ Given $G(s)$

Example 2. For $G(s) = e^{-\tau s}/s^2$, the previous lecture gave

$$x(kh+h) = \Phi x(kh) + \Gamma_1 u(kh-h) + \Gamma_0 u(kh)$$

$$\Phi = \begin{pmatrix} 1 & h \\ 0 & 1 \end{pmatrix} \quad \Gamma_1 = \begin{pmatrix} \tau \left(h - \frac{\tau}{2} \right) \\ \tau \end{pmatrix} \quad \Gamma_0 = \begin{pmatrix} \frac{(h-\tau)^2}{2} \\ h-\tau \end{pmatrix}$$

With $h = 1$ and $\tau = 0.5$, this gives

$$H(z) = C(zI - \Phi)^{-1}(\Gamma_0 + \Gamma_1 z^{-1}) = \frac{0.125(z^2 + 6z + 1)}{z(z^2 - 2z + 1)}$$

Order: 3

Poles: 0, 1, and 1

Zeros: $-3 \pm \sqrt{8}$

34

Examples in Matlab

```
>> Phi = [0.5 -0.2; 0 0];
>> Gamma = [2; 1];
>> C = [1 0];
>> D = 0;
>> h = 1;
>> H = ss(Phi, Gamma, C, D, h);
>> zpk(H)
```

```
>> % From cont-time transfer function to discrete-time
>> % pulse transfer function
>> s = zpk('s');
>> G = 1/s^3;
>> H = c2d(G,h)
```

```
>> % Another way
>> G = tf([1],[1 3 2 0]);
>> G = ss(G);
>> H = c2d(G,h);
>> tf(H)
```

35